



Engineered in Europe.
Made for the World.

Sunmaxx PX-1 Premium PVT-Module



Highest efficiency and space-saving:

The simultaneous generation of electricity and heat enables a higher total efficiency.

Flexible operation:

For use on roofs or open spaces. From residential buildings to industrial buildings to cold local heating networks.

Combination with heat pumps and geothermal energy:

By using PVT-Modules, heat pumps can be operated more efficiently, and geothermal probes can be regenerated.

Generates more electricity:

Thanks to the cooling of the PVT-module, an increase of 5 - 10 % of the electrical yield can be achieved.

Plug & Play:

Installation-friendly connectors make it easy to connect the electrics and hydraulics.

Sustainability:

The aluminium heat exchanger on the back is optimised to save material and is easily recyclable. Produced with 100 % independently certified green electricity.

Address:

Sunmaxx PVT GmbH
Schutterwälder Str. 13,
01458 Ottendorf-Okrilla
Germany

Contact:

+49 35205 69401 0
office@sunmaxx-pvt.com
www.Sunmaxx-pvt.com

Made in Europe:

Our modules are manufactured in the EU to the highest quality standards.

Completely carefree:

10 years Product Guarantee

25 years linear performance guarantee
(electrical power)

97 % after the 1st year,

80 % after the 25th year

Specifications Sunmaxx PX-1

GENERAL	UNIT	
Dimensions	[mm]	1,755 x 1,147 x 40
Weight	[kg]	29
Front	-	Highly transparent solar glass ESG (3.2 mm)
Heat exchanger	-	Aluminium-Alloy
Frame	-	Anodised aluminium, black

ELECTRICAL DATA	UNIT	385 W	390 W	395 W	400 W
Type	-	108 M10 Mono half cell PERC			
Nominal PV power *	[W]	385	390	395	400
Voltage MPP V_{MPP}	[V]	31.21	31.40	31.60	31.8
Current MPP I_{MPP}	[A]	12.34	12.42	12.50	12.58
Open circuit voltage V_{OC}	[V]	37.05	37.17	37.29	37.41
Short circuit current I_{SC}	[A]	12.94	13.02	13.10	13.18
Efficiency	[%]	19.2	19.5	19.7	20.0
Max. system voltage V_{DC}	[V]	1,000			
Cooling Gain **	[%]	5 – 10			
Backsheet	-	Polymer foil black			
Connection	-	3-part junction box according to IEC 62790, MC4 original connector according to EN 62852			

THERMAL DATA	UNIT	
Thermal energy ***	[W]	1,200
Thermal carrier medium	-	Water-glycol mixture
Volume thermal carrier medium	[l]	0.7
Pressure drop ****	[mBar]	29
Hydraulic connection	-	Plug in connector with flexible tube
Testing pressure	Bar	6
Operating pressure	Bar	1 – 2
Specific flow	[l/h]	50 – 150
Stagnation temperature	°C	81
Thermal collector efficiency: η_0 *****	-	0.76 / 0.60 (V_{OC} / M_{PP})

* STC Conditions

** Estimation without obligation

*** Radiation: 1000 W/m², Volume Flow: 144 l/h, Temperature: 25 °C, Wind speed: 0 m/s, Delta T = 0 Kelvin, MPP measuring

**** 100 l/h, 20 °C (water)

***** Radiation: 1000 W/m², Volume Flow: 144 l/h, Temperature: 25 °C, Wind speed: 0 m/s, Delta T = 0 Kelvin 0,76 corresponds to 1,522 W, 0,6 corresponds to 1,200 W

Measurement accuracy P_{MPP} at STC -3/+3% | Tolerance remaining electrical values -10/+10%

Certification: Solar Keymark (in progress)